

COMMERCIAL VAN

NEW

ENDURO 616



Comfort



Mileage



Fuel efficient

Features	Benefits
Optimized weight construction	▶ Reduces fuel consumption and provides high comfort
Vertical grooves and open horizontal grooves arrangement	▶ Provide excellent wet and dry grip
Reinforced belt construction with two steel belts and full nylon protector	▶ Provide high load and speed capacity and good safety margins
New bead design	▶ Reduces heat build up in high load conditions and extends the life of the tyre





ENDURO 616

Size Range

Specifications may change without notice

Inch	Series	Tyre Size	Load Index	Speed Rating	UTQG	Tread Depth	Overall Diameter	PLY RATING	MAX. LOAD (KG)	Side Wall
						mm	mm			
16	60	195/60R16C LT	99/97	H	-	12	640	6PR	775/730	BSW
	65	195/65R16C LT	104/102	T	-	12	660	8PR	900/850	BSW
	65	205/65R16C LT	107/105	T	-	12	672	8PR	975/925	BSW
	65	215/65R16C LT	109/107	R	-	12	686	8PR	1030/975	BSW
	65	225/65R16C LT	112/110	T	-	13	698	8PR	1120/1060	BSW
	65	235/65R16C LT	115/113	R	-	14	712	8PR	1215/1150	BSW
	75	175/75R16C LT	101/99	R	-	12	668	8PR	825/775	BSW
	75	185/75R16C LT	104/102	R	-	12	684	8PR	900/850	BSW
	75	195/75R16C LT	107/105	R	-	12	698	8PR	975/925	BSW
	75	205/75R16C LT	110/108	R	-	13	714	8PR	1060/1000	BSW
	75	215/75R16C LT	116/114	R	-	13	728	10PR	1250/1180	BSW
15	65	205/65R15C LT	102/100	T	-	12	647	6PR	850/800	BSW
	70	195/70R15C LT	104/102	R	-	12	655	8PR	900/850	BSW
	70	205/70R15C LT	106/104	R	-	12	669	8PR	950/900	BSW
	70	215/70R15C LT	109/107	S	-	13	683	8PR	1030/975	BSW
	70	225/70R15C LT	112/110	R	-	13	697	8PR	1120/1060	BSW
14	-	185R14C LT	102/100	R	-	12	650	8PR	850/800	BSW
	-	195R14C LT	106/104	R	-	12	666	8PR	950/900	BSW
	65	175/65R14C LT	90/88	T	-	12	584	6PR	600/560	BSW
	70	165/70R14C LT	89/87	R	-	11	588	6PR	580/545	BSW
	75	215/75R14C LT	112/110	R	-	13	678	8PR	1120/1060	BSW

BSW Black Side Wall UTQG Uniform Tyre Quality Grade