



HIGHWAY RIB

M111Z



Developed for the front-axle position, the M111Z delivers uniform contact pressure owing to a flatter crown radius. Its zig-zag ribs with wider grooves enhance steering stability on both wet and dry roads.

Rim Dia.	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
							OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
□ □ □ □ □	315/80 R22.5	154/150M	-	TL	BL	14.4	1079	312	502	339	9.00	9.00 - 9.75
	295/80 R22.5	152/148M	-	TL	BL	14.9	1050	303	488	328	9.00	8.25 - 9.00
	13 R22.5	154/149L	-	TL	BL	15.8	1123	313	522	341	9.00	9.00 - 9.75
	12 R22.5	152/147M	-	TL	BL	14.9	1081	295	503	322	9.00	8.25 - 9.00
	11 R22.5	148/145M	-	TL	BL	15.0	1052	277	489	304	8.25	7.50 - 8.25

□: Three ribs design
 [TYPE] TL: TUBELESS
 [SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.