



## M131

This rib-type highway tire has been developed for all positions use on commercial vehicles. Its uniform tread wear and special tread compound ensure long tire life and high-speed durability. The M131, with its straight ribs, multi-sipes on the edge of each rib and U-shaped grooves, improves wet performance exceptionally.

Rim Dia.	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEAGUIDING	ALTERNATE
							OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)	MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
16	700 R16	117/116L	-	TT	BL	11.0	778	192	362	214	5.50	5.00 - 6.50
	700 R16	113/112L	-	TT	BL	11.0	778	192	362	214	5.50	5.00 - 6.50
	700 R16	108/106L	-	TT	BL	11.0	778	192	362	214	5.50	5.00 - 6.50
	650 R16	108/107L	-	TT	BL	10.6	747	172	347	190	4.50	4.50 - 5.50
15	700 R15	-	12	TT	BL	11.0	752	192	350	214	5.50	5.50
	700 R15	-	8	TT	BL	11.0	752	192	350	214	5.50	5.50
	700 R15	105/101L	-	TL	BL	11.0	752	192	350	214	5.50	5.50

[TYPE] TT: TUBE TYPE, TL: TUBELESS [SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.