

M140Z



The M140Z, TOYO TIRES' highway rib, has been developed to emphasize its improved wear performance and retreadability in a wide variety of operating conditions ranging from short, middle to long highway hauls. Its new casing construction, profile, functional straight rib tread appearance and compound designed under DSOC II, TOYO TIRES' advanced tire design technology, contribute to M140's excellent performance over the competitors.

| Rin Dia | | TIRE SIZE | LOAD INDEX/ SPEED SYMBOL | PLY RATING | TYPE | SIDE WALL | TREAD DEPTH (mm) | INFLATED DIMENSION | | LOADED DIMENSION | | | |
|------------|-----|-------------|-----------------------------------|---------------|------|--------------|------------------------|----------------------|-----------------------|-----------------------|----------------------|-------------------------|-------------------------|
| | | | | | | | | OVERALL DIA. (mm) | OVERALL WIDTH (mm) | STATIC RADIUS (mm) | STATIC WIDTH (mm) | MEASURING RIM (Inch) | ALTERNATE RIM (Inch) |
| 17 | 7.5 | 225/90R17.5 | 127/125L | - | TL | BL | 12.3 | 855 | 233 | 398 | 257 | 6.75 | 6.00 - 6.75 |
| | | 825 R16 | 128/126L | - | TT | BL | 12.3 | 855 | 227 | 398 | 252 | 6.00 | 6.50 |
| 1 | 6 | 825 R16 | - | 14 | TT | BL | 12.3 | 855 | 227 | 398 | 252 | 6.00 | 6.50 |
| | | 750 R16 | 123/121L | - | TT | BL | 11.7 | 803 | 209 | 373 | 228 | 6.00 | 5.50 - 6.50 |

[TYPE] TT: TUBE TYPE, TL: TUBELESS [SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.