



HIGHWAY RIB M143



The M143 has been developed under DSOC II, TOYO TIRES' advanced tire design technology, to deliver excellent overall performance in severe operating conditions. It has been designed especially for excellent wear performance and improved casing durability.

Rim Dia.	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
							OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
17.5	235/75 R17.5	132/130M	-	TL	BL	13.0	803	233	362	254	6.75	6.75 - 7.50
	225/75 R17.5	129/127M	-	TL	BL	13.0	793	225	358	245	6.75	6.00 - 6.75
	215/75 R17.5	126/124M	-	TL	BL	12.5	776	212	352	231	6.00	6.00 - 6.75
	205/75 R17.5	124/122M	-	TL	BL	12.1	761	202	346	220	6.00	5.25 - 6.75
	9.5 R17.5	129/127L	-	TL	BL	11.6	838	230	376	251	6.75	6.00 - 6.75

[TYPE] TL: TUBELESS

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.