

M53



This rib-type highway tire for all positions features its wider tread with a special compound that gives a long tread life. The tapered shoulder of the M53 improves handling while its strong steel belt improves safety.

	Rim Dia.	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION			
								OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)	MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
	16	750 R16	121/120L	-	TT	BL	11.5	806	210	375	231	6.00	5.50 - 6.50
		750 R16	114/112L	-	TT	BL	11.5	806	210	375	231	6.00	5.50 - 6.50
		700 R16	116/111M	-	TT	BL	11.0	777	195	361	220	5.50	5.50
-[15	700 R15	105/101L	-	TT	BL	11.0	752	192	350	214	5.50	5.00 - 6.50
		195 R15C	106S	-	TL	BL	9.7	693	196	317	207	5.50	5.00 - 6.00

□: M53A, △: M53B

[TYPE] TT: TUBE TYPE, TL: TUBELESS [SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.