



PW01

**All Position
On/Off & Mixed Service**



Features

Combination of rib & lug pattern

Special cut & chip compound

Tread compound

Benefit

- ▶ Excellent traction and maneuverability
- ▶ Provides resistance to cutting and tearing
- ▶ Long tread life

SIZE RANGE

TYRE SIZE	PR	LOAD INDEX	SPEED RATING	APPROVED RIM	OUTER DIAMETER (mm)	MAX. LOAD (KG)	MAX. PRESSURE (KPA)	TREAD DEPTH (mm)
8.25R20	14PR	136/134	M	6.5	974	2240/2120	830/830	14
9.00R20	16PR	144/142	K	7	1019	2800/2650	900/900	15
10.00R20	16PR	146/143	K	7.5	1054	3000/2725	830/830	16
11.00R20	18PR	152/149	K	8	1085	3550/3250	930/930	16.5
11.00R20	16PR	150/147	K	8	1085	3350/3075	830/830	15.5
12.00R20	18PR	154/151	K	8.5	1125	3750/3450	830/830	17
11R22.5	16PR	148/144	M	8.25	1054	3150/2800	830/830	15.8
13R22.5	18PR	154/150(156/150)	L(K)	9.75	1124	3750/3350	790/790	16.8
315/80R22.5	20PR	156/153	J	9	1076	4000/3650	850/850	16.8
11R24.5	16PR	149/146	M	8.25	1104	3250/3000	830/830	15.8
12.00R24	18PR	156/153	K	8.5	1225	4000/3650	790/790	17
12.00R24	20PR	160/156	K	8.5	1225	4500/4000	900/900	17