



# PW212



## Steer/Trailer Regional Service



### Features

- Five rib design
- Wide straight grooves
- Crossing sips in intermediate ribs
- Equal rib distribution

### Benefit

- ▶ Excellent handling and maneuverability
- ▶ Exceptional water evacuation for wet traction
- ▶ Enhance traction and tread life
- ▶ Tread scrubbing resistance

## SIZE RANGE

TYRE SIZE	PR	LOAD INDEX	SPEED RATING	APPROVED RIM	OUTER DIAMETER (mm)	MAX. LOAD (KG)	MAX. PRESSURE (KPA)	TREAD DEPTH (mm)
215/75R17.5	12PR	126/124	M	6	767	1700/1600	724/724	12.5
215/75R17.5	16PR	135/133	J	6	767	2180/2060	860/860	12.5
235/75R17.5	14PR	132/130	M	6.75	797	2000/1900	760/760	13.5
235/75R17.5	16PR	143/141	J	6.75	797	2725/2575	860/860	13.5
225/70R19.5	14PR	128/126	J	6.75	811	1800/1700	760/760	14.3
245/70R19.5	16PR	136/134	M	7.5	839	2240/2120	830/830	14.1
265/70R19.5	16PR	140/138	M	7.5	867	2500/2360	790/790	13.4
285/70R19.5	16PR	146/144(144/142)	L(M)	8.25	895	3000/2800	900/900	13.4
295/75R22.5	14PR	144/141	M	9	1014	2800/2575	760/760	17.5
255/70R22.5	16PR	140/137(140/140)	M(L)	7.5	930	2500/2300	830/830	14.1
11R22.5	16PR	148/145	M	8.25	1054	3150/2900	830/830	17.2